

Cylinder Capacity	3.5 ft ³ / 99 L
Cylinder Materials	Aluminum or Composite (0.29/0.3 L)
Cylinder Length w/1 st Stage Regulator	Aluminum 12.73 in / 32.33 cm Composite 13.34 in / 33.88 cm
Working Pressure	3,000 PSI / 207 BAR 4,500 PSI / 310 BAR
Low Pressure Hose Length	20 in / 50.8 cm
First Stage Hose Connection	360-degree swivel
Regulator First Stage	Unbalanced piston
Regulator Second Stage	Unbalanced
System Weight	Approximately 2.5 lbs / 1.36 kg
Buoyancy Full	Approximately -2.0 lbs / -.9 kg

FEATURES

- Ready for action - the Advantac Down-Exhaust EBS is purpose built for emergency helicopter egress. Simply bite down on the mouthpiece and place nose clip to breathe underwater
- Ergonomic nose clip integrated into the 2nd stage body for rapid deployment with either left or right hand
- 360° braided swivel hose for swift manipulation
- Light-weight and minimal profile
- Integrated pressure gauge indicates pressure
- Designed for ease of service and repair
- Built using quality marine grade materials

OPTIONS

- 3000 PSI (207 bar) or 4500 PSI (310 bar) configurations
- Aluminum or composite cylinder (0.29 L)
- ON/OFF knob or hex key lock
- Pressure gauge available in Metric or Imperial
- Multiple hose lengths



APAC Exclusive Authorized Distributor:

Aerosafe PTE LTD
"Safety is our concern"

Aerosafe Pte Ltd.

Address: 700 West Camp Road, Unit 06-03, JTC Aviation One, Singapore 797649

Telephone: +65 6481 8278

Email: Sales@aerosafe.com.sg

Sep 2022

Cylinder Capacity	3.5 ft³ / 99 L
Cylinder Materials	Aluminum or Composite (0.29/0.3 L)
Cylinder Length w/1 st Stage Regulator	Aluminum 12.73 in / 32.33 cm Composite 13.34 in / 33.88 cm
Working Pressure	3,000 PSI / 207 BAR 4,500 PSI / 310 BAR
Low Pressure Hose Length	20 in / 50.8 cm
First Stage Hose Connection	360-degree swivel
Regulator First Stage	Unbalanced piston
Regulator Second Stage	Unbalanced
System Weight	Approximately 2.5 lbs / 1.36 kg
Buoyancy Full	Approximately -2.0 lbs / -.9 kg

FEATURES

- Ready for action - the Advantac Side-Exhaust EBS is purpose built for emergency helicopter egress
- Ergonomic second stage ready for rapid deployment with either left or right hand
- 360° braided swivel hose for swift manipulation
- Light-weight and minimal profile
- Integrated pressure gauge indicates pressure
- Designed for ease of service and repair
- Built using quality marine grade materials

OPTIONS

- 3000 PSI (207 bar) or 4500 PSI (310 bar) configurations
- Aluminum or composite cylinder (0.29 L)
- ON/OFF knob or hex key lock
- Pressure gauge available in Metric or Imperial
- Multiple hose lengths



APAC Exclusive Authorized Distributor:

Aerosafe PTE LTD
"Safety is our concern"

Aerosafe Pte Ltd.

Address: 700 West Camp Road, Unit 06-03, JTC Aviation One, Singapore 797649
Telephone: +65 6481 8278
Email: Sales@aerosafe.com.sg